

FM-3000 SERIES ANTI-FATIGUE SPONGE VINYL**I. Description**

Static Technologies' FM-3000 Series Sponge vinyl floor mat is a highly resilient material that provides outstanding anti-fatigue benefits in an economical ESD control floor mat. This homogeneous PVC nitrile compound provides significantly better anti-fatigue properties than sponge vinyl. The mat's resiliency exerts upward pressure against the foot, providing true ergonomic support.

FM-3000 mats are classified as a static dissipative material per The ESD Association guidelines. The grey mat has an embossed surface for traction. The closed cell sponge material is easy to clean and lies flat.

II. Specifications

Surface Resistivity: 10^9 to 10^{10} ohms

Point-To-Ground Resistance (R_{TG}): 10^9 to 10^{10} ohms per EOS/ESD-S4.1

Static Decay: < 0.1 sec. Per FTMS 101C, M4046

Temperature Use Range: 30° to 150° F

Thickness: 0.375"

Weight: .9 pounds per square foot

Snaps: One installed 10mm socket snap on

Color: Grey

III. Sizes

FM-3005:

3' x 5' mat with one 10mm socket snap installed

FM-3060:

3' x 60' roll stock, no hardware

Custom sizes are available (3' width).

IV. Cleaning

Use mild soap and water to clean common dirt and grime from mat surface. Wipe away excess soapy water with clean cloth or mop. Do not use cleaners containing silicone. Rinse with clean water.

All statements, technical information and recommendations related to the seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Static Technologies Corporation ♦ 61 Pleasant Street ♦ Randolph, MA 02368 U.S.A.

Telephone: 781-961-7220

Email: statictech@xensei.com

Fax: 781-961-1858

Website: www.static-tech.com