

FLOOR MAT GROUND CORDS

I. Description

These ground cords provide an effective and convenient means of grounding ESD control floor matting. The snap is an industry standard 10mm stud. The snap is encased in a molded dome shaped housing that reduces tripping hazards. The low profile also helps prevent accidental disconnection of the ground cord caused by foot traffic or the movement of carts and equipment.

Static Technologies floor mat ground cords terminate in a #10 ring terminal for connection to hard ground. Units are available with or without one megohm resistors.

II. Specifications

Cord Length: 15'

Ground Connection: #10 ring terminal

Snap: 10mm (3/8") Stud

Snap Housing: Molded low profile black ABS plastic

Wire: 65 Strand high flex 18AWG tinned copper

Wire Insulation: Black polyurethane

III Part Numbers

P/N	LENGTH	TERMINATION	RESISTOR
GC-2001	15'	#10 ring	1 megohm
GC-2002	15'	#10 ring	none
GC-2005	6'	banana plug	none



GC-2001, GC-2002



GC-2002 ground cord with banana plug

The GC-2002 has a 6' cord and banana plug termination for a variety of grounding set-ups including:

Use with SP-1001 ground point/ground monitor for a quick and convenient grounding connection for floor mats

Use with GC-16104 bench mount to connect table mat to wrist strap ground point

All statements, technical information and recommendations related to the seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.