

WB-8000 SERIES SPEIDEL® WRIST STRAP

I. Description

Static Technologies' Speidel wrist strap uses the widely recognized Speidel Twist-O-Flex metal band to create an effective, comfortable, and durable ESD control grounding device. These bands come in three standard sizes. The metal band is clad in black Tedlar® to create an insulative exterior.

Non-tangling coiled cords with excellent retractile qualities come in 6' and 12' lengths. A 6' cord with 90° right angle banana plug for under-the-bench mounting systems is also available. Wrist straps include an alligator clip.

Speidel and Twist-O-Flex are registered trademarks of Speidel Textron. Tedlar is a registered trademark of DuPont.

II. Band Specifications

Band Material: Stainless steel Twist-O-Flex band clad in black Tedlar

Sizes:

- Small fits wrists 6.25" to 9.50" in circumference
- Medium fits wrists 7.25" to 10.75" in circumference
- Large fits wrists 7.75" to 11.75" in circumference.

Snap Assembly: 4mm (1/8") stud

Wristband Interior Resistivity: <100 ohms

III. Cord Specifications

Banana Plug: Fits standard 0.165" diameter jack

Break Force: > 28 pounds

Resistor: 1/4 watt, one megohm, carbon film

Snap Assembly: 4mm (1/8") socket

Wire: 7 strands of tinsel wire

Wire Insulation: Black polyurethane

IV. Part Numbers

P/N	Cord	Size
WB-8010	Wristband only	Small
WB-8011	Wristband only	Medium
WB-8012	Wristband only	Large
WB-8050	6' Standard	Small
WB-8051	6' Standard	Medium
WB-8052	6' Standard	Large
WB-8080	12' Standard	Small
WB-8081	12' Standard	Medium
WB-8082	12' Standard	Large
WB-8090	6' 90° Angle	Small
WB-8091	6' 90° Angle	Medium
WB-8092	6' 90° Angle	Large

All statements, technical information and recommendations related to the seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.